

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

1. (Currently Amended) An actuator comprising:

a casing;

a stationary member which has a coil member and is mounted in the casing; and

a movable member which includes a moving element and is supported by the casing;

wherein the moving element has a shaft and is supported by the casing so as to be moved in an axial direction of the shaft and in a rotational direction having the axial direction of the shaft as its rotational axis;

wherein electric current is caused to flow through the coil member such that the moving element is moved in the axial direction and in the rotational direction;

wherein the stationary member includes a first stationary member that imparts to the movable member a force oriented in the axial direction and a second stationary member that imparts to the movable member a force oriented in the rotational direction;

wherein the first stationary member includes a pair of first stationary elements provided symmetrically with respect to the rotational axis and the second stationary member includes a pair of second stationary elements provided symmetrically with respect to the rotational axis; and

P26498.A06

wherein the coil member includes a first coil member that excites a first magnetic path passing through the first stationary member and a second coil member that excites a second magnetic path passing through the second stationary member;

wherein the first stationary member imparts to the moving element the force oriented in the axial direction and the second stationary member imparts to the moving element the force oriented in the rotational direction;

wherein the moving element includes a magnet member having a magnetization direction substantially orthogonal to the axial direction;

wherein the first coil member includes a pair of first coils each provided in each of the first stationary elements and the second coil member includes a pair of second coils each provided in each of the second stationary elements; and

wherein the first coils excite the first stationary elements in an antiphase excitation mode, respectively and the second coils excite the second stationary elements in an antiphase excitation mode, respectively.

2. (Canceled)

3. (Currently Amended) The actuator as claimed in Claim [[2]] 1, wherein the magnet member of the moving element is disposed symmetrically with respect to the rotational axis.

4. (Canceled)

5. (Currently Amended) The actuator as claimed in Claim [[4]] 1, wherein the first stationary elements and the second stationary elements are disposed such that an axial plane containing the first stationary elements and an axial plane containing the second stationary elements intersect with each other substantially orthogonally.

6. (Currently Amended) The actuator as claimed in Claim [[4]] 1, wherein the magnet member of the moving element includes two magnets having opposite magnetization directions, respectively and each of the first stationary elements is formed by a substantially E-shaped magnetic part having three magnetic pole portions arranged in the axial direction.

7. (Original) The actuator as claimed in Claim 6, wherein each of the second stationary elements is formed by a substantially C-shaped magnetic part having two magnetic pole portions arranged in the axial direction.

8. (Previously Presented) The actuator as claimed in Claim 7, wherein opposite end portions of each of the first stationary elements and opposite end portions of each of the second stationary elements overlap each other when viewed in the axial direction.

9. (Original) The actuator as claimed in Claim 8, wherein a gap is formed between

P26498.A06

each of the magnetic pole portions of each of the first stationary elements and each of the magnetic pole portions of each of the second stationary elements.

10. (Original) The actuator as claimed in Claim 7, wherein an end portion of each of the magnets of the moving element is rotated so as to traverse each of two recesses among the magnetic pole portions of each of the first stationary elements.

11. (Previously Presented) The actuator as claimed in Claim 7, wherein the magnets of the moving element are formed into an identical size;

wherein the magnets are provided such that not only opposed end faces of the magnets are brought into contact with each other in the axial direction, but other end faces of the magnets opposite to the contacting opposed end faces are axially flush with axial opposite end faces of each of the first stationary elements, respectively.

12. (Canceled)

13. (Previously Presented) An actuator comprising:

a casing;

a stationary member which has a coil member and is mounted in the casing;

a movable member which includes a moving element and is supported by the

casing; and

a rotational resonant spring that effects resonant motion of the moving element in

P26498.A06

the rotational direction, which is provided between the moving element and the casing;

wherein the moving element has a shaft and is supported by the casing so as to be moved in an axial direction of the shaft and in a rotational direction having the axial direction of the shaft as its rotational axis;

wherein electric current is caused to flow through the coil member such that the moving element is moved in the axial direction and in the rotational direction;

wherein the stationary member includes a first stationary member that imparts to the movable member a force oriented in the axial direction and a second stationary member that imparts to the movable member a force oriented in the rotational direction; and

wherein the coil member includes a first coil member that excites a first magnetic path passing through the first stationary member and a second coil member that excites a second magnetic path passing through the second stationary member.

14. (Currently Amended) An actuator comprising:

a casing;

a stationary member which has a coil member and is mounted in the casing;

a movable member which includes a moving element and is supported by the casing; and

a spring member which includes a first spring provided between the casing and the moving element, a second spring provided between the moving element and the further moving element and a third spring provided between the further moving element and the casing

P26498.A06

such that the first, second and third springs are deflectable in the axial direction;

wherein the moving element has a shaft and is supported by the casing so as to be moved in an axial direction of the shaft and in a rotational direction having the axial direction of the shaft as its rotational axis;

wherein electric current is caused to flow through the coil member such that the moving element is moved in the axial direction and in the rotational direction;

wherein the stationary member includes a first stationary member that imparts to the movable member a force oriented in the axial direction and a second stationary member that imparts to the movable member a force oriented in the rotational direction;

wherein the coil member includes a first coil member that excites a first magnetic path passing through the first stationary member and a second coil member that excites a second magnetic path passing through the second stationary member; and

wherein the movable member further includes a further moving element disposed coaxially with the moving element and movable in the axial direction;

wherein the first stationary member and the second stationary member impart to one of the moving element and the further moving element the force oriented in the axial direction and the force oriented in the rotational direction, respectively;

wherein the one of the moving element and the further moving element includes a magnet member disposed symmetrically with respect to the rotational axis and having a magnetization direction substantially orthogonal to the axial direction;

wherein the first stationary member includes a pair of first stationary elements

P26498.A06

provided symmetrically with respect to the rotational axis and the second stationary member includes a pair of second stationary elements provided symmetrically with respect to the rotational axis;

wherein the first coil member includes a pair of first coils each provided in each of the first stationary elements and the second coil member includes a pair of second coils each provided in each of the second stationary elements;

wherein the first coils excite the first stationary elements in an antiphase excitation mode, respectively and the second coils excite the second stationary elements in an antiphase excitation mode, respectively;

wherein the magnet member of the one of the moving element and the further moving element includes two magnets having opposite magnetization directions, respectively, with the one of the moving element and the further moving element undergoing the force oriented in the axial direction from the first stationary member; and

wherein each of the first stationary elements is formed by a substantially E-shaped magnetic part having three magnetic pole portions arranged in the axial direction.

15 – 20. (Cancelled)

21. (Currently Amended) The actuator as claimed in Claim [[19]] 14, wherein the magnet member of the one of the moving element and the further moving element includes two magnets having opposite magnetization directions, respectively, with the one of the moving

P26498.A06

element and the further moving element undergoing the force oriented in the rotational direction from the second stationary member;

wherein each of the second stationary elements is formed by a substantially C-shaped magnetic part having two magnetic pole portions arranged in the axial direction.

22. (Currently Amended) The actuator as claimed in Claim [[20]] 24, wherein the magnet member of the other of the moving element and the further moving element includes two magnets having opposite magnetization directions, respectively, with the other of the moving element and the further moving element undergoing the force oriented in the rotational direction from the second stationary member;

wherein each of the second stationary elements is formed by a substantially C-shaped magnetic part having two magnetic pole portions arranged in the axial direction.

23. (Currently Amended) The actuator as claimed in Claim [[19]] 14, wherein an end portion of each of the magnets is rotated so as to traverse each of two recesses among the magnetic pole portions of each of the first stationary elements.

24. (New) An actuator comprising:

a casing;

a stationary member which has a coil member and is mounted in the casing;



a movable member which includes a moving element and is supported by the casing; and

a spring member which includes a first spring provided between the casing and the moving element, a second spring provided between the moving element and the further moving element and a third spring provided between the further moving element and the casing such that the first, second and third springs are deflectable in the axial direction;

wherein the moving element has a shaft and is supported by the casing so as to be moved in an axial direction of the shaft and in a rotational direction having the axial direction of the shaft as its rotational axis;

wherein electric current is caused to flow through the coil member such that the moving element is moved in the axial direction and in the rotational direction;

wherein the stationary member includes a first stationary member that imparts to the movable member a force oriented in the axial direction and a second stationary member that imparts to the movable member a force oriented in the rotational direction;

wherein the coil member includes a first coil member that excites a first magnetic path passing through the first stationary member and a second coil member that excites a second magnetic path passing through the second stationary member;

wherein the movable member further includes a further moving element disposed coaxially with the moving element and movable in the axial direction;

wherein the first stationary member imparts to one of the moving element and the further moving element the force oriented in the axial direction and the second stationary

P26498.A06

member imparts to the other of the moving element and the further moving element the force oriented in the rotational direction;

wherein each of the moving element and the further moving element includes a magnet member disposed symmetrically with respect to the rotational axis and having a magnetization direction substantially orthogonal to the axial direction;

wherein the first stationary member includes a pair of first stationary elements provided symmetrically with respect to the rotational axis and the second stationary member includes a pair of second stationary elements provided symmetrically with respect to the rotational axis;

wherein the first coil member includes a pair of first coils each provided in each of the first stationary elements and the second coil member includes a pair of second coils each provided in each of the second stationary elements;

wherein the first coils excite the first stationary elements in an antiphase excitation mode, respectively and the second coils excite the second stationary elements in an antiphase excitation mode, respectively;

wherein the magnet member of the one of the moving element and the further moving element includes two magnets having opposite magnetization directions, respectively, with the one of the moving element and the further moving element undergoing the force oriented in the axial direction from the first stationary member; and

wherein each of the first stationary elements is formed by a substantially E-shaped magnetic part having three magnetic pole portions arranged in the axial direction.